



serie  
**UR-61**



**COLLARÍN UNIVERSAL CON SALIDA BRIDA**  
UNIVERSAL INTAKE RING WITH FLANGED OUTLET



CUERPO BODY		BANDA STRAP			
REF.	SALIDA OUTLET	REF.	DN TUBO DN PIPE	Ø MIN.	Ø MAX.
UR-61-050	DN-50	2 BANDAS/STRAPS			
UR-61-065	DN-60/65	2 BANDAS/STRAPS			
		UR-63-088-130	80-100	88	130
		UR-63-133-159	125	133	159
		UR-63-159-192	150	159	192
		UR-63-190-220	200	190	220
		UR-63-216-254-A		216	254
		UR-63-267-316-A	250	267	316
		UR-63-318-368-A	300	318	368
		UR-63-368-435-A	350	368	435
		UR-63-426-466-A	400	426	466
* Necesita alargaderas / Extensions needed		UR-63-473-510-A	450	473	510
* Necesita alargaderas / Extensions needed		UR-63-505-554-A	500	505	554
* Necesita alargaderas / Extensions needed		UR-63-557-606		557	606
* Necesita alargaderas / Extensions needed		UR-63-610-668-A	600	610	668
* Necesita alargaderas / Extensions needed		UR-63-668-726		668	726
* Necesita alargaderas / Extensions needed		UR-63-708-754-A	700	708	754
* Necesita alargaderas / Extensions needed		UR-63-760-805		760	805
UR-61-DN080	DN-80	2 BANDAS/STRAPS			
		UR-63-133-159	125	133	159
		UR-63-159-192	150	159	192
		UR-63-190-220	200	190	220
		UR-63-216-254-A		216	254
		UR-63-267-316-A	250	267	316
		UR-63-318-368-A	300	318	368
		UR-63-368-435-A	350	368	435
		UR-63-426-466-A	400	426	466
		UR-63-473-510-A	450	473	510
* Necesita alargaderas / Extensions needed		UR-63-505-554-A	500	505	554
* Necesita alargaderas / Extensions needed		UR-63-557-606		557	606
* Necesita alargaderas / Extensions needed		UR-63-610-668-A	600	610	668
* Necesita alargaderas / Extensions needed		UR-63-668-726		668	726
* Necesita alargaderas / Extensions needed		UR-63-708-754-A	700	708	754
* Necesita alargaderas / Extensions needed		UR-63-760-805		760	805
UR-61-DN100	DN-100	2 BANDAS/STRAPS			
		UR-63-159-192	150	159	192
		UR-63-190-220	200	190	220
		UR-63-216-254-B		216	254
		UR-63-267-316-B	250	267	316
		UR-63-318-368-B	300	318	368
		UR-63-368-435-A	350	368	435
		UR-63-426-466-A	400	426	466
		UR-63-473-510-A	450	473	510
		UR-63-505-554-B	500	505	554
		UR-63-557-606		557	606
* Necesita alargaderas / Extensions needed		UR-63-610-668-A	600	610	668
* Necesita alargaderas / Extensions needed		UR-63-668-726		668	726
* Necesita alargaderas / Extensions needed		UR-63-708-754-A	700	708	754
* Necesita alargaderas / Extensions needed		UR-63-760-805		760	805
* Necesita alargaderas / Extensions needed		UR-63-805-850-A	800	805	850

REF.	DENOMINACIÓN DESCRIPTION
UR-61-ALARGA	Alargadera Extension

\* 2 alargaderas por banda / 2 extensions per strap

CUERPO BODY		BANDA STRAP			
REF.	SALIDA OUTLET	REF.	DN TUBO DN PIPE	Ø MIN.	Ø MAX.
UR-61-DN125	DN-125	2 BANDAS/STRAPS			
		UR-63-216-254-B	200	216	254
		UR-63-267-316-B	250	267	316
		UR-63-318-368-B	300	318	368
		UR-63-368-435-B	350	368	435
		UR-63-426-466-B	400	426	466
		UR-63-473-510-B	450	473	510
		UR-63-505-554-B	500	505	554
		UR-63-557-606	500	557	606
		UR-63-610-668-B	600	610	668
		UR-63-668-726	600	668	726
UR-61-DN150-A	DN-150	3 BANDAS/STRAPS			
		UR-63-318-368-B	300	318	368
		UR-63-368-435-B	350	368	435
		UR-63-426-466-B	400	426	466
		UR-63-473-510-B	450	473	510
		UR-63-505-554-B	500	505	554
		UR-63-557-606	500	557	606
UR-61-DN150-B	DN-150	3 BANDAS/STRAPS			
		UR-63-505-554-B	500	505	554
		UR-63-557-606		557	606
		UR-63-610-668-B	600	610	668
		UR-63-668-726		668	726
		UR-63-708-754-B	700	708	754
		UR-63-760-805		760	805
		UR-63-805-850-B	800	805	850
		UR-63-900-950	900	900	950
UR-61-DN200-A	PN-10	4 BANDAS/STRAPS			
UR-61-DN200-B	PN-16	4 BANDAS/STRAPS			
		UR-63-473-510-B	450	473	510
		UR-63-505-554-B		505	554
		UR-63-557-606	500	557	606
		UR-63-610-668-B	600	610	668
		UR-63-668-726		668	726
		UR-63-708-754-B	700	708	754
		UR-63-760-805		760	805
		UR-63-805-850-B	800	805	850
		UR-63-900-950	900	900	950
		UR-63-1000-1050	1.000	1.000	1.050

- Amplia gama de diámetros que cubre tubos desde 88 hasta 1.050 milímetros.
- Presión de trabajo PN-10 y PN-16.
- Fundición nodular GGG-50.
- Revestimiento EPOXI de 250µ.
- Tornillería inoxidable y junta de goma EPDM.
- Banda de acero inoxidable de 60 mm. de ancho, con tuerca inoxidable y goma EPDM.
- No apto para tubos de PE y PVC-O.

- Wide range of diameters covering pipes from 88 to 1.050 mm.
- PN-10 and PN-16 operating pressure.
- GGG-50 nodular cast iron.
- 250µ EPOXY coating.
- Equipped with stainless steel bolts and washers, and EPDM rubber seal.
- Stainless steel straps 60 millimeters width equipped with stainless steel nuts and EPDM rubber.
- Not suitable for PE and PVC-O pipes.

**UR-cast**  
Water Fittings

www.ur-cast.com  
Tfno: (+34) 945 200 466 - Fax: (+34) 945 249 867  
C/ Urartea nº 15-17, pab. 6-10, P. I. ALI GOBEO / 01010 VITORIA-GASTEIZ / ÁLAVA (Spain)